



MOBILE PLASMA STAND CONFIDENCE MONITOR

Models MPS-ACM/MPS-MCM

SPECIFICATION DATA

DA-LITE SCREEN COMPANY, INC.
 3100 North Detroit Street
 Post Office Box 137
 Warsaw, Indiana 46581-0137
 Phone: 574-267-8101
 800-622-3737
 Fax: 574-267-7804
 Toll Free Fax: 877-325-4832
 www.da-lite.com
 e-mail: info@da-lite.com

SUGGESTED SPECIFICATIONS: Da-Lite/Advance Confidence Monitor model MPS _____. The stand shall be a fabricated mild steel design and consist of a welded base, welded top frame, two columns, electric tilt mechanism (MPS-ACM only) hydraulic tilt mechanism (MPS-MCM only), and universal plasma mount. The base shall be a MIG welded assembly fabricated with 1 1/2" x 2" x 11ga and 2" x 2" x 14 ga wall tubing. The top frame shall be a MIG welded assembly fabricated with 1 1/2" x 2" x 11ga and 2" x 2" x 14 ga wall tubing. Two columns shall be fabricated with 1 3/4" x 1 3/4" x 16 ga wall tubing and have protected openings for cord concealment. The universal plasma mount shall be fabricated from 11ga CR sheet and securely attach to the top frame for vertical adjustment. The automated stand shall use radio frequency remote controlled components that operate on 110V AC 60Hz electric power to control the backward tilt from 15° through 50° from vertical. The manual stand shall use a hand operated hydraulic pump and valve to control the backward tilt from 15° through 50° from vertical. Mount shall have a commercial powder coat black finish.

Specification Data

Model	Nominal Height to Top of Plasma	Allowable Plasma Mount Points	Maximum Plasma Weight	Power Supply Required
MPS-ACM	42"	1 5/8"-26 1/2" horizontal and 0"-16" vertical	130#	110 VAC 60Hz
MPS-MCM	42"		130#	manual

Optional Mount Accessories:

- Concealment skirt (black)

